Automatic Parking System with 5 Million Times Operation Lifetime 6m Max Boom Length

Basic Information

- Place of Origin:
- Brand Name:
- Model Number:
- Price:
- Supply Ability:
- CBG, CBG 18B

Guangdong, China

- \$360.00/sets 1-99 sets
- 2000 Piece/Pieces per Month



Product Specification

- Max Length Of Boom:
- Voltage:
- Inslation Class:
- Warranty:
- Operation Lifetime:
- Output Power:
- Feature:
- Altitude:
- Port:
- Highlight:

DC24V F 2 Years >=5 Million Times 120W Durable 1000M Or Lower


6 Meter

Shenzhen

1000m automatic parking system, 1000m automatic barrier gate, 6m Max Boom Automatic Parking System



More Images



Company Profile


Shenzhen Chengbang Mechanical and Electrical Industry Co., Ltd, We have strong scientific technology, first-class produced lines, advanced gear testing centers and high-precision advanced equipment, imported CNC gears which are ahead of our peers in terms of quality. In pursuit of high quality products, excellent reputation, continuous innovation and development and perfect after-care service, we d launched a series of diversified products.



Our advantages:

- 1. NO MOQ limit.
- 2. Customized LOGO.
- 3. 24 Hours delivery for stock
- 4. 2 Year warranties.
- 5. New model every year.

Products Description



Our Product Introduction

Current:6A


Operation Lifetime:>=5million times

Temperature Range:-40°C to +60°C (temperatures below -20°C require a heating element)

Applications: Generally suited for controlling gates leading to highways and expressways, as well as vehichle-plate reading systems for gated communities and commercial parking lots.





Different color to choose



Max length of boom is 6 Meter

Interior structure





Power Supply

Old and New Product's Difference



Before:

1) Worm gear, general appearance

2) The previous products use with Rv50 reducer and added the splint to compose the movement. The worm gear is a consumable product. After using a long time, there will be a large gap, the pole will be not stable and shake so will cause the gear reducer to grind.

3)The products mainly used with AC 220V motor, the fixed speed was not adjustable.

4) Open structure, a low degree of protection, easy to enter water.

5) AC220V.

6) During installation, needs to adjusted the magnet position to ensure the door opening angle. After a long time, the shaking will affect the limit position or the pole may be deviated downwards.



After:

1) Gear transmission structure, beautiful appearance, compact structure, strong overall sense.

2) The new products are tailor-made for this industry and the gear adopts the processing technology of worm grinding wheel grinding after heat treatment, fine rolling of hard alloy hob, etc., the accuracy grade \geq GB / T100951, 2-2001 7 level.

3)The new product uses with DC brushless motor to avoid the problem of carbon brush life. Adjustable speed.

4)The entire seal structure, high degree of protection (\geq IP55); have a rainproof capability.

5) DC24V(Safe voltage)

6) Installed the chassis, adjust the position automatically after power on, and adjust the angle of rising pole and falling pole at will.

The packaging of 18B unit motor







3.Seal the carton with tape

1.Put polyurethane foam inside

2.Cover with plastic and put the motor into the carton

Single net weight about : 43KG(Don't include the boom arm)

Single package carton size: 108.5X38X34CM Package Type: Carton or Wooden case

Factory View





Visit factory



Exhibition



Enterprise Qualification



Qiantou Xinxing Industrial Zone, Niushan community, Dongcheng District, Dongguan City