DC 24V Security Traffic Control Toll Gate Boom Barrier Motor 140W Output Power


Basic Information

• Place of Origin: Guangdong, China

• Brand Name: CBG, CBG

Model Number: 18B

Price: \$114.00/pieces 1-99 pieces
 Packaging Details: One carton for 1pcs 18B motor.
 Supply Ability: 2000 Piece/Pieces per Month



Product Specification

Warranty: 2 YearsVoltage: DC24V

• Operation Lifetime: >=5 Million Times

Output Power: 140W
Color: Optional
Weigh: 16KG
Port: Shenzhen

High Light: OEM Car Parking Automatic Gate Motor,

LED Arm Car Parking Automatic Gate Movement, Servo Motor Car Park Security

Gate Mechanisms

• Highlight: Toll Gate Boom Barrier Motor,

Boom Barrier Motor DC 24V, Boom Barrier Motor 140W



Insulation Class: F
Gate Operation Time: 0.3Operation Lifetime: 0.5Working Environment
Temperature Range: -40°C
[-40°F-+140°F]
(temperatures below -20°
require a heating element

Generally suited for controlling gates leading to highways and expressways as well as vehicle-plate reading systems for gated communities and commercia parking lots.

More Images





Product Description

DC 24V Security Traffic Control Toll Gate Boom Barrier Motor With 140W Output Power

Company Profile

The operation of the DC barrier gate is simple, and the speed of the take-off and landing rod is determined according to the speed ratio of the reducer.







Products Description

DC Brush-Less Single Unit Operating Mechanism





Product Parameters

Voltage: DC24V

Output Efficiency: 120W

Current: 6A

Insulation Class: F

Gate Operation Time: 0.3~5s

Operation Lifetime: ≥ 5 million times

Working Environment

Temperature Range: -40°C~+60°C

[-40°F~+140°F]

(temperatures below -20°C/-4°F


require a heating element)

Humidity: 85% or lower Altitude: 1000M or lower

Applications

Generally suited for controlling gates leading to highways and expressways, as well as vehicle-plate reading systems for gated communities and commercial parking lots.

Functions & Features





The packaging of 18B unit motor







1.Put polyurethane foam inside

Cover with plastic and put the motor into the carton

3.Seal the carton with tape

Single net weight: 16kg

Single package carton size: 38.5X20.8X25CM Package Type: Carton or Wooden case

Old and New Product's Difference



Before:

- 1) Worm gear, general appearance
- 2) The previous products use with Rv50 reducer and added the splint to compose the movement. The worm gear is a consumable product. After using a long time, there will be a large gap, the pole will be not stable and shake so will cause the gear reducer to grind.
- 3)The products mainly used with AC 220V motor, the fixed speed was not adjustable.
- 4) Open structure, a low degree of protection, easy to enter water.
- 5) AC220V.
- 6) During installation, needs to adjusted the magnet position to ensure the door opening angle. After a long time, the shaking will affect the limit position or the pole may be deviated downwards.



After:

- 1) Gear transmission structure, beautiful appearance, compact structure, strong overall sense.
- 2) The new products are tailor-made for this industry and the gear adopts the processing technology of worm grinding wheel grinding after heat treatment, fine rolling of hard alloy hob, etc., the accuracy grade \geq GB / T100951, 2-2001 7 level.
- 3)The new product uses with DC brushless motor to avoid the problem of carbon brush life. Adjustable speed.
- 4)The entire seal structure, high degree of protection (\geq IP55); have a rainproof capability.
- 5) DC24V(Safe voltage)
- 6) Installed the chassis, adjust the position automatically after power on, and adjust the angle of rising pole and falling pole at will.

Factory View



Assembly Equipment







Visit Factory













Exhibition



Enterprise Qualification



















CBG Shenzhen Chengbang Electromechancal Industry Limited





mok_1szcb_cbg@163.com



automaticbarriersgates.com