18B Parking Barrier Mechanism for Road and Traffic Barriers at Altitudes up to 1000M

Basic Information

- Place of Origin:
- Brand Name:
- CBG, CBG
- Model Number:
- Minimum Order Quantity:
- Price:
- Guangdong, China
- 18B
- 2 pieces
 - \$160.00/pieces 2-99 pieces



Product Specification

- Warranty:
- Voltage:
- Inslation Class:
- Operation Lifetime:
- Output Power:
- Feature:
- Color:
- Altitude:

• Highlight:

- Special Features:
- DC24V F >=5 Million Times 140W Durable Optional

2 Years

- 1000M Or Lower
- Waterproof / Weatherproof 1000m barrier gate motor, 1000m dc24v road gate motor, 140w barrier gate motor



More Images Ρ Îai

Company Profile

Shenzhen Chengbang Mechanical and Electrical Industry Co., Ltd. was established in 2010, located in Guangdong China. The factory with 50,000 square meter areas and more than 50 experienced employees which supply ability is 2000pcs per month. We are the professional manufacturer for vehicle entrance management system and equipment (Swinging door operating mechanism, Brush-less gate motor, DC brush-less single unit operating mechanism, Commercial gate operating mechanism and so on). We have strong scientific technology, first-class produced lines, advanced gear testing centers and high-precision advanced equipment, imported CNC gears which are ahead of our peers in terms of quality. In pursuit of high quality products, excellent reputation, continuous innovation and development and perfect after-care service, we d launched a series of diversified products.



Products Description

DC Brush-Less Single Unit Operating Mechanism



Product Parameters

Voltage: DC24V Output Efficiency: 120W Current: 6A Insulation Class: F Gate Operation Time: $0.3 \sim 5s$ Operation Lifetime: ≥ 5 million times Working Environment Temperature Range: $-40^{\circ}C \sim +60^{\circ}C$ [$-40^{\circ}F \sim +140^{\circ}F$] (temperatures below $-20^{\circ}C/-4^{\circ}F$ require a heating element) Humidity: 85% or lower Altitude: 1000M or lower

Applications

Generally suited for controlling gates leading to highways and expressways, as well as vehicle-plate reading systems for gated communities and commercial parking lots.



The packaging of 18B unit motor







3.Seal the carton with tape

1.Put polyurethane foam inside

2.Cover with plastic and put the motor into the carton

Single net weight: 16KG

Single package carton size: 38.5X20.8X25CM Package Type: Carton or Wooden case

Old and New Product's Difference



Before:

1) Worm gear, general appearance

2) The previous products use with Rv50 reducer and added the splint to compose the movement. The worm gear is a consumable product. After using a long time, there will be a large gap, the pole will be not stable and shake so will cause the gear reducer to grind.

3)The products mainly used with AC 220V motor, the fixed speed was not adjustable.

4) Open structure, a low degree of protection, easy to enter water.

5) AC220V.

6) During installation, needs to adjusted the magnet position to ensure the door opening angle. After a long time, the shaking will affect the limit position or the pole may be deviated downwards.

Factory View



After:

1) Gear transmission structure, beautiful appearance, compact structure, strong overall sense.

2) The new products are tailor-made for this industry and the gear adopts the processing technology of worm grinding wheel grinding after heat treatment, fine rolling of hard alloy hob, etc., the accuracy grade \geq GB / T100951, 2-2001 7 level.

3)The new product uses with DC brushless motor to avoid the problem of carbon brush life. Adjustable speed.

4)The entire seal structure, high degree of protection (\geq IP55); have a rainproof capability.

5) DC24V(Safe voltage)

6) Installed the chassis, adjust the position automatically after power on, and adjust the angle of rising pole and falling pole at will.



Assembly Equipment



Visit Factory



Exhibition



Entreprise Qualification

