Guangdong, China

\$268.00/pieces 2-99 pieces

CBG

21B

## Boom Barrier Gate For Safe And Vehicle Access Management In Commercial And Industrial Sectors

#### **Basic Information**

• Place of Origin:

CBG®

- Brand Name:
- Model Number:
- Minimum Order Quantity: 2 pieces
- Price:



#### Product Specification

<ul> <li>Material:</li> </ul>	Steel
Motor:	DC,120W, 24V, Torque Motor
<ul> <li>Working Temperature:</li> </ul>	-35°C+ 75°C
• Speed:	0.8S, 1.5S, 3S(ACCPRDING
Application:	Over-sized Traffic Flow Area, Transit Solution, Outdoor, Tolling Solution, Parking Solution
Case Size:	250*300*990mm
Highlight:	Industrial Boom Barrier Gate, Commercial Boom Barrier Gate, Vehicle Access Management Boom Barrier Ga

# 120W Power Supply Road Safety Barrier Parking Boom Barrier Gate For Entrance And Exit

### **Product Description**

### Overview

With the widespread use of vehicles and the increase in multi-storey buildings, many security weaknesses have occurred in today's modern life. For people residing on high floors, situations such as disconnection from the outside create a great risk in terms of security. At the same time, security problems also occur in areas where vehicles are gathered at a single point, such as parking lots of buildings and shopping centers. With automatic barrier gate systems, security can be easily ensured as every movement


#### Product description

1.-The traffic barrier is widely used for the facilities of parking, traffic or toll system.

2.-Arms can be chosen from 1 meters to 6 meters.

- 3.-This type of barrier could match with direct boom( pole), fold boom Or fence boom..
- 4. When power off, we can lift up the boom arm by hand directly
- 5.-All the process is soft without any noise and shaking.
- 6.-Housing color: yellow,red ,blue,black,white (optional)
- 8.-Boom arm direction can be chosen leftward to rightward.
- 8.-Auto warming up, suitable for cold environment.

#### Parameters



#### **Technical Parameters**

Size	330*270*1020mm
Power supply	DC 24V
Open/close speed	0.3s to 6s
Working temperature	-30~60°C
Rated power	140w
Motor rated speed	1500r/min
Humidity	<=85%
Remote control distance	30 m
Max boom length	6m
External power	220V 50/60HZ

## Product picture



#### interior structure:



Big torque motor **Collision resistant motor** 

### **Toll station motor**

# MCBF more 5 million times

#### Fast response

Packing & Delivery

## The packaging of 18B unit motor





1.Put polyurethane foam inside

2.Cover with plastic and put the motor into the carton



3.Seal the carton with tape



To better ensure the safety of your goods, professional, environmentally friendly, convenient and efficient packaging services will be provided.

## **Boom barrier projects**





## Exhibition



Certification

