Automatic Car Park Barriers Automatic Parking Barrier Gate Automatic Parking Barrier Gate

Basic Information

Place of Origin: Guangdong, China

Brand Name: CBGModel Number: 18BMinimum Order Quantity: 1pieces



Product Specification

Ip Degree: IP44 Power Consumption: 140w

• Lifetime: More Than 10 Million Or 10 Years

 Arm Type: Straight Arm, Fence Arm And Folding Arm
Keyword: Saudi Arabia Barrier Gate,Inverter Motor Automated Boom Barrier Parking Barrier

Gate

Optional Accessories: Photocell, Loop Detector, Traffic Light

Car Parking: Vehicle Control Barriers Gate

Service: OEM/ODM Available
Highlight: Automatic Parking Barrier,

Automatic Car Park Barriers, Automatic Parking Barrier Gate

Product Description

120W Power Supply Road Safety Barrier Parking Boom Barrier Gate For Entrance And Exit

Product Description


Overview

A boom barrier goes by many names. Sometimes called a barrier arm, a boom, a boom gate, or an access barrier arm; these all mean the same thing. A boom barrier arm is a gate or access point that regulates traffic flow by means of a long arm that pivots on the opener. The arm is also called a boom. This might be familiar to anyone that has used a microphone before since this term is also used for the arm that holds a microphone. The opener or operator is the entire structure that moves the arm up and down. They come in many different shapes and sizes depending on the application and where they will be installed.

Product description

- 1.-The traffic barrier is widely used for the facilities of parking, traffic or toll system.
- 2.-Arms can be chosen from 1meters to 6 meters.
- 3.-This type of barrier could match with direct boom(pole), fold boom Or fence boom..
- 4. When power off, we can lift up the boom arm by hand directly
- 5.-All the process is soft without any noise and shaking.
- 6.-Housing color: yellow,red ,blue,black,white (optional)
- 8.-Boom arm direction can be chosen leftward to rightward.
- 8.-Auto warming up, suitable for cold environment.

Parameters



Parameters

Power supply	DC24V
Control Board	DC brushless controller
Input power	220V,56/60hz
Power	120W
Lifting/ down way	Remote control or manual
Remote control distance	>30m
Types of arm	fold ,straight ,fence
Arm length	max 6m straight boom
Motor rated speed	1500r/min
Working temperature	-30~+60
Protect level	IP55
Humidity	85%

interior structure:



Big torque motor **Collision resistant motor**

Toll station motor

MCBF more 5 million times

Fast response

Packing & Delivery

The packaging of 18B unit motor







2.Cover with plastic and put the motor into the carton



3.Seal the carton with tape



To better ensure the safety of your goods, professional, environmentally friendly, convenient and efficient packaging services will be provided.

Boom barrier projects





Exhibition



Certification



















CBG Shenzhen Chengbang Electromechancal Industry Limited





