RS485 Communication Interface Automatic Boom Barrier 3/4/5 Meters for Parking Lot Management and Security

Basic Information

Brand Name: CBGCertification: CEModel Number: 21B



Product Specification

Barrier Arm: 3/4/5metersMaterial: Aluminum Alloy

• Working Frequency: 50/60Hz

• Product Application: Parking Lot, Toll Gate, Industrial Zone

Entrance

• Warranty: 1 Year

• Operating Temperature: -35°C-75°C

• Product Communication RS485

Interface:

• Working Temperature: -35°C+ 75°C

• Highlight: 5 Meters Boom Barrier, 3 Meters Boom Barrier,

4 Meters Boom Barrier



Product Description:

An Automatic Boom Barrier is an essential security solution for controlling vehicle access in various locations, ensuring effective traffic — management and enhanced security. This Electric Boom Lift is designed to operate efficiently and reliably, providing a convenient way to control vehicle entry and exit.

The Boom Barrier Gate comes with a warranty of 1 Year, offering peace of mind and assurance of product quality and durability. The installation method for this barrier is Surface Mounting, making it suitable for a wide range of locations and applications. With a Product Communication Interface of RS485, the Boom Barrier provides a reliable and stable connection for seamless communication and control. This interface ensures smooth operation and integration with different access control systems. Operating within a wide temperature range of -35°C to +75°C, this Boom Barrier is built to withstand harsh weather conditions, making it ideal for both indoor and outdoor use. Its durability and resilience ensure consistent performance even in extreme temperatures. The Barrier Arm of the Boom Barrier comes in various lengths of 3, 4, or 5 meters, offering flexibility to suit different entry points and traffic requirements. This versatility allows for customization based on specific site needs and traffic volume.

Features:

Automatic Boom Barrier

Car Park Boom Gate

Barrier Arm Gates

Product Name: Boom Barrier Material: Aluminum Alloy

Operating Temperature: -35°C-75°C

Product Application: Parking Lot, Toll Gate, Industrial Zone Entrance

Working Temperature: -35°C+ 75°C
Product Communication Interface: RS485

Technical Parameters:

Working Frequency	50/60Hz
Operating Temperature	-35°C-75°C
Warranty	1 Year
Material	Aluminum Alloy
Installation Method	Surface Mounting
Working Temperature	-35°C+ 75°C
Barrier Arm	3/4/5 meters
Product Communication Interface	RS485
Product Application	Parking Lot, Toll Gate, Industrial Zone Entrance

Applications:

The CBG 21B Electric Boom Lift Barrier Gate is a high-quality product originating from China, featuring a CE certification for reliability and safety. Designed for surface mounting, this boom barrier is suitable for a wide range of application occasions and scenarios. With an operating temperature range of -35°C to 75°C, the CBG 21B is ideal for use in various environments, including parking lots, toll gates, and industrial zone entrances. Its robust construction and durable materials ensure long-lasting performance, making it a dependable solution for managing vehicle access and traffic control.

The product communication interface of RS485 allows for seamless integration with different systems, enabling efficient and effective operation. Whether installed in a busy highway sound barrier or a commercial parking facility, the CBG 21B delivers reliable performance and enhanced security.

Customers can have peace of mind with the 1-year warranty that comes with the CBG 21B Electric Boom Lift Barrier Gate, providing assurance of quality and support. Its versatility and durability make it a versatile solution for various applications, offering convenience and security in a wide range of scenarios.

Customization:

Customize your Barrier Arm Gates with our Product Customization Services for the CBG 21B model. Originating from China, this product is made of high-quality Aluminum Alloy, ensuring durability and strength. With a CE certification, it meets international standards for safety and quality.

Operating smoothly in temperatures ranging from -35°C to 75°C, these Electric Boom Lift gates are reliable in various weather conditions. The installation method for these gates is Surface Mounting, providing ease of setup and use.

Choose from barrier arms of 3, 4, or 5 meters to suit your specific needs. Additionally, the product comes with a 1-year warranty, giving you peace of mind regarding the quality and performance of your Barrier Arm Gates.

Support and Services:

Product Technical Support and Services for Boom Barrier:

Our technical support team is available to assist you with any questions or issues you may have regarding the operation and maintenance of your Boom Barrier. Whether you need help troubleshooting a problem or require guidance on setting up the barrier, our experts are here to help.

In addition to technical support, we also offer a range of services to our customers, including installation assistance, on-site maintenance, and training programs to ensure that you get the most out of your Boom Barrier.

CBG Shenzhen Chengbang Electromechancal Industry Limited

+8615017905059



mok_1szcb_cbg@163.com



automaticbarriersgates.com

Qiantou Xinxing Industrial Zone, Niushan community, Dongcheng District, Dongguan City